

U-REPAIR

Urethane Repair System

**Automatic-mixing two part urethane • No guesswork or messy measuring
Repair, bond & seal virtually any surface • Fast setting • No downtime • No
solvents or VOCs • No odours • No shrinkage • Hot-Cold resistant • No Drip •
Sandable, grindable, paintable, drillable & tapable**

**Custom
Formulation
Available**

*Call with your
Specific needs*

Also available in a
universal cartridge
(Fits single barrel
caulking guns)

Available in various
hardness (60A – 98A),
Custom colours
& specific curetimes

Automatic
Mixing tip
Ensures perfect mixing



Various application tips available
1" & 2" Fan-tail, 1/2" wide flat bead, V-groove

Dual Dispensing
Automatic Mixing Unit

**Sets in as
little as
60 seconds**

*Available in most
cure-time requirements*

Ideal for :

Conveyor Belt repair

Fabric and Steel Cable Belts
PVC and Urethane Belts
Belt Lacing and Clip Covering

Elastomeric Repairs

Rubber Lining
Urethane Linings
Pulley Lacing • Pump Liners
Off-Road and Forklift Tires

Concrete repair

Floors • Containments
Walls, cracks, spalling
Expansion Joints
Threading and Mounting

WARANTY

U-REPAIR is warranted to perform as claimed under normal circumstances. This warranty is limited to the replacement of defective product or to refund the purchase price of material if proven defective.

STORAGE

U-REPAIR has a shelf life of 12 months when stored properly in unopened packages at 18 °C – 30 °C. Do not expose to moisture. Opened product will remain good for 60 days.

SIZE / COLOURS

U-REPAIR is available in black (standard), white, concrete gray, clear, green, blue, orange, yellow, tan & red or we'll match your custom colour. Available in easy use : 200 x 200 ml (430 gms.) sizes. Other sizes available upon request.

Protecting the Future – Today

TUCKTHANE.com

Phone: 450-746-2799
Toll-Free: 1-866-584-2799